China

CMC

COA

Cylinder/Tank

N2

Gas N2 Nitrogen For Packaging & Controlled Atmospheres Production Storage

Basic Information

Place of Origin:

- Brand Name:
- Certification:
- Model Number:

Our Product Introduction

for more products please visit us on gascylindertank.com

- Minimum Order Quantity: 1 ton
- Price: US \$40/ton
- Packaging Details:
- Delivery Time: 15 days
- Payment Terms: L/C, T/T
- Supply Ability: 20000 Tons/Year



Product Specification

- Product Name:
- Melting Point:
- Appearance:
- Boiling Point:
- Cylinder Pressure:
- Valve:
- Cylinder Standard:
- Transport Package:
- Specification:
- Trademark:
- Origin:
- HS Code:
- Supply Ability:
- CAS No.:
- Formula:

Colorless, Odorless -196 ºC

Nitrogen Gas

-209.86 °C

- 12.5MPa/15MPa/20MPa
- Qf-2/Cga580
- GB/ISO/DOT
- Sea Transportation
- 10L 40L 50L
- CMC
- Suzou, China
- 2804300000
- 50000piece/Month
- 7727-37-9 N2



More Images







Product Description

Nitrogen gas (N2) is a colorless, odorless, and tasteless gas that makes up about 78% of Earth's atmosphere. It is an essential element for life and plays a crucial role in various natural and industrial processes.

Here are some key points about nitrogen gas:

Composition and Properties: Nitrogen gas is composed of two nitrogen atoms chemically bonded together. It has a molecular weight of 28.0134 grams per mole and a density of 1.251 grams per liter at standard temperature and pressure (STP).

Abundance in the Atmosphere: Nitrogen gas is the most abundant gas in Earth's atmosphere, accounting for approximately 78% of its total volume. It exists in a diatomic form (N2), meaning two nitrogen atoms are strongly bonded together.

Role in Supporting Life: Nitrogen is an essential element for living organisms. However, most organisms cannot use nitrogen in its gaseous form directly. Nitrogen-fixing bacteria and certain plants can convert gaseous nitrogen into more usable forms like ammonia (NH3) or nitrate (NO3-) through a process called nitrogen fixation. These compounds can then be utilized by other organisms to build proteins and nucleic acids.

Industrial Applications: Nitrogen gas has numerous industrial applications due to its inert properties. It is commonly used as a blanketing gas to displace oxygen and prevent oxidation or combustion in various processes, such as in the food and beverage industry, electronics manufacturing, and chemical production. Nitrogen gas is also used in the production of ammonia, fertilizers, and as a coolant in cryogenic applications.

Liquid Nitrogen: When nitrogen gas is cooled below its boiling point of -195.8 degrees Celsius (-320.4 degrees Fahrenheit), it condenses into a liquid form known as liquid nitrogen. Liquid nitrogen is extremely cold and is commonly used in cryogenics for freezing and preserving biological samples, as well as in various scientific and medical applications.

Safety Precautions: While nitrogen gas itself is not toxic, it can displace oxygen in a confined space, leading to an oxygen-deficient environment. This can be dangerous if proper precautions are not taken. Oxygen monitoring and adequate ventilation should be ensured when working with nitrogen gas or any other inert gases.

It's worth noting that nitrogen gas is distinct from nitrous oxide (N2O), commonly known as "laughing gas," which is also a compound containing nitrogen but with different properties and uses.

| Basic Info. | | | | | |
|---|-----------|---------------------|------------------|--|--|
| Model NO. | N2 | Storage Medium | Flammable/Toxic | | |
| Pressure Level High Pressure (10.0MPa≤p<100.0MPa) Condition New | | | | | |
| Pressures | 20MPa | OTC | OTC | | |
| Size | 40L 50L | Transport Package | Sea | | |
| Specification | 40L 20MPA | Trademark | CMC | | |
| Origin | suzhou | Production Capacity | 50000piece/Month | | |
| | | | | | |

Detailed

Photos



Outside diameter(mm) Water capacity(L) Design wall Thickness(mm)

| 219mm | 36-40L 20L-34L | 5.7 |
|-----------------|---|-------------------|
| 229mm(GB/ISO) | 27L 30L 40L 50L | 5.7 |
| 232mm(GB/ISO) | 40L 47L 50L 40L | 6 |
| 232mm(GB/ISO) | 40L 47L 50L | 5.4 |
| 232mm(GB/ISO) | 40-50L | 5.8 5.4 5.2 |
| 232mm(ISO) | 40-50L 60L | 5.8 |
| 279mm(ISO) | 68L 80L 50-54L | 6.0 |
| 267mm(GB5099.1) | 60L 68L 70L 80L 50-54L 60L | 5.7 |

267mm(ISO)

6.2

68L 70L 80L

Company

Profile

ShangHai CMC chemical Co.,Itd. is staffed by trained personnel, combine many years experience in Gas industry .We supply cylinder gas, electronic gas, etc., and the gas holder, panel, valves and fittings and other equipment, parts and engineering services to our customers in China and worldwide; The products are involved in various industrial fields, such as semiconductor chip, solar cell, LED, TFT-LCD, optical fiber, glass, laser, medicine, etc., Our mission is to partner with our global customers to provide support, solutions and quality products that are innovative, reliable, and safe.

Our products mainly include: H2, O2, N2, Ar, CO2, propane, acetylene, helium, laser mixed gas, SiH4, Sih2cl2, SiHCL3, SiCL4, NH3, CF4, NF3, SF6, HCL, N2O, doping mixed gas (TMB, PH3, B2H6) and other electronic gases.

| -,,,,,,,,,,,,,- | , ., ., |
|-----------------|---------------------------------|
| SiCl4 NH3 NH3 | CH3F SiH4 Kr H2S WF6 F6+Cl2 |
| 4MS C3F8 C3F8 | TEOS CH4 PH3 SF6 C2 HCI+Ne |
| CF4 C4F8 SiH2 | TMB+H2 |
| SiF4 C3H8 CI2 | He +As |
| BBr3 C3H6 DCE | Ge+Se |
| POCI3 N2 SO2 | D+B |
| BCI3 D2 CO2 | CO+NO |
| SiHCI3 CH2F2 HF | AsH3 C2H4 C2H2 HBr COS Ar+O2 |
| TMAI DMZn DEZn | GeH4 C2H6 B2H6 H2Se GeCl4 Xe+NO |

Workshop Display:

